



8	FEC012-BK	DISCHARGE HOSE 4.5/5.0/7.0KG	RUBBER HOSE	1
7	FEC117-PS-EN	PULL TAG BROOKS-EN	P.P	1
6	FEC116-MS	SAFETY PIN	CHROME MILD STEEL	1
5	FEC067-MS-050-ZP	SYPHON TUBE 5.0KG AS 510.0MM	3/8" X 1/8" M/STEEL TUBE	1
4	FEC067-MS-020-ZP	SYPHON TUBE 2.0KG AS 375.0MM	3/8" X 1/8" M/STEEL TUBE	1
3	FEX002-MS-TP2-ZP	2.0KG. WALL BRACKET	GALV. MILD STEEL	1
2	FEC175-PS-070-BK	DISCHARGE HORN 3.5KG & 5.0KG AS	PLASTIC	1
1	FEC175-PS-022-BK	DISCHARGE HORN 2.0KG AS	PLASTIC	1
	FEC180-CS-050-RD	CO2 CYLINDER 5.0KG (RED)	CARBON STEEL	1
	FEC180-CS-020-RD	CO2 CYLINDER 2.0KG (RED)	CARBON STEEL	1
	FEC059-GM	CO2 VALVE (FRONT OUTLET - 3.5/5KG AS)	BRASS	1
	FEC060-GM	CO2 VALVE (SIDE OUTLET - 2.0KG AS)	BRASS	1

TECHNICAL SPECIFICATION

ARTICLE NO.	1041551	1041552
CAPACITY	2.0KG	5.0KG
OVERALL WEIGHT ±5.0%	7.7KG	17.0KG
OVERALL DIAMETER ±5.0 (φA)	φ114.0	φ138.0
OVERALL HEIGHT ±5.0 (φB)	530.0	740.0
VOLUME ±0.5	3.0L	7.5L
TEST PRESSURE	250 BAR	
WORKING PRESSURE	70 BAR AT 20°C	
DISCHARGE TIME	8 - 12 SEC	13 - 17 SEC
TEMPERATURE RANGE	-20°C TO 60°C	
MEDIA	CARBON DIOXIDE (CO2)	
FILLING DEVIATION	±5.0 % BY MASS	

* - WEIGHT WITHOUT WALL BRACKET

UNLESS OTHERWISE STATED
DIMENSION IN MILLIMETRES

TOLERANCE
LINEAR ±0.2
ANGULAR :

FINISH :
RED

REVISION : 03

DRN. :
APPD. 1 :
APPD. 2 :
ISSUED : 20 MAR 2019
DRN. NO. : CEEUCSO - VTK
PART NO. :

QA ENG. :
QA MGR :
FAC. MGR :
20 MAR 2019
CCEUCSO - VTK

STEEL RECON IND. SDN. BHD.
PRODUCT :
EURO FIRE EXTINGUISHER

TITLE :
CO2 EURO ASSEMBLY
(STEEL CYLINDER)

